




ineo 5000i

- > Black & white A4 printer
- > Up to 50 ppm

Option diagram







Media output Convenience stapler EH-C591

Finishing functionalities





Duplex

Corner stapling (offline)

Description

Media Input

PF-P23 Paper tray	250 sheets; A5–A4; 60–120 g/m²
PF-P24 Paper tray	520 sheets; A5–A4; 60–120 g/m²
SCD-5000x Copier desk	Provides storage space for print media and
	other materials

Media output

EH-C591 Convenience stapler 20-sheet off-line stapling

Technical specifications

System Specifications

STSTEM STEELITICATIONS		
Panel size/resolution	1.8"	
System memory	512 MB (standard/max)	
(standard/max)		
Interface	10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11	
	b/g/n	
Network protocols	TCP/IP (IPv4 / IPv6); LPD; IPP; SNMP; HTTP; HTTP(S)	
Paper input capacity	570 sheets / 1,610 sheets (standard/max)	
(standard/max)		
Paper Tray 1	1x 520 sheets; A6–A4; 60–120 g/m²	
opt. Paper Tray 1 - Total	1x 250 sheets; A5–A4; 60–120 g/m² (up to 3x)	
opt. Paper Tray 2 - Total	1x 520 sheets; A5–A4; 60–120 g/m² (up to 2x)	
Manual bypass	50 sheets; A6–A4; custom sizes; 60–200 g/m²	
Automatic duplexing	A4; 60–105 g/m²	
Output Capacity (standard)	250	
Print volume (monthly)	Rec. 10,000 pages; Max. 150,000 pages	
Toner lifetime	Black up to 20,000 pages	
Imaging unit lifetime	50,000	
Power consumption	220–240 V / 50/60 Hz; Less than 770 W	
System dimension (W x D x H)	400 x 396 x 288 mm (without options)	
System weight	Approx. 13.2 kg (without options)	

PRINTER SPECIFICATIONS

Imaging technology	Laser
Toner technology	Polymerized Toner
Print resolution	1,200 x 1,200 dpi
Print Speed A4 (mono/colour)	Up to 50 ppm
1st print out time A4	7.5 sec.
(mono/colour)	
Warm-up time	Approx. 25 sec.
Page description language	PCL 6 (XL3.0); PostScript 3; XPS
Operating Systems	Windows 7 (32/64); Windows 8.1 (32/64);
	Windows 10 (32/64); Windows Server 2008 (32/64);
	Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019;
	Macintosh OS X 10.10 or later; Linux
Printer fonts	85 PCL Latin; 66 PostScript 3 Emulation Latin
Mobile Printing	Mopria (Android); Google Cloud Print; WiFi Direct
System Features	
Security Functions	SSL2; SSL3 and
(standard)	TLS1.0/1.1/1.2 network communication;
	IPsec support; IEEE 802.1x support;
	Secure print; Kerberos
Accounting Functions	Active Directory support
(standard)	(user name + password + e-mail + smb folder)
Accounting Functions	ID card authentication (ID card reader)
(optional)	
Software	Net Care Device Manager; Web Connection;
	Driver Packaging Utility

























DEVELOP

Konica Minolta Business Solutions Europe GmbH



Virgilio 1315, C1407 BQY, Buenos Aires. - 54-11-4648-4347 / 54-11-4648-3558

- All specifications refer to A4-size paper of 80 g/m² quality.
- All specifications refer to A4-size paper of 80 g/m² quality.
 The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
 The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
 Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
 DEVELOR and long are registered trademarks (product titles owned by Konica Minolta Business Solution).
- DEVELOP and ineo are registered trademarks/product titles owned by Konica Minolta Business Solutions Europe GmbH.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.

 All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.